

CLG

CLG HYDRAULIC SEQUENCE VALVE



NOTE

If the flow volume of the incoming pressure side is too much, there is a possibility that the proper sequential procedures would not work. In this instance, use a flow control valve to adjust flow volume from the pressure source.

ORDERING INDICATION

CLG-3A(5.0MPa)

CLG	系列 Series	CLG
3	Sequential action pressure adjustment range 3: 1.0~6.0 MPa 6: 5.0~18.0MPa	
A	A	A Manifold type
5.0MPa	Set pressure(Set valve for sequence operating pressure)	Provide a difference of more than 1MPa between operating and setting pressure. When using multiple CLG sequence valves in a parallel fashion, provide each set pressure with a pressure difference more than 1MPa.

SPECIFICATION

MODEL	SEQUENTIAL ACTION PRESSURE ADJUSTMENT RANGE(MPa)	OPERATING PRESSURE RANGE(MPa)	ADJUSTING SCREW TURN RATIO(MPa/REV)	CRACKING PRESSURE (MPa)	OPERATING TEMPERATURE(°C)	USABLE FLUID
CLG-3A	1.0~6.0	2.0~35.0	1.0	0.01	0~70°C	General Hydraulic Oil Equivalent to ISO-VG-32
CLG-6A	5.0~18.0	6.0~35.0	2.8	0.01	0~70°C	

